



DRAWING (mm)



AC induction motor and gearbox also sold separately.



PHOTO



MODEL NO. DESIGNATION

AI-015W - Voltage - Phase - Connection
 Example: AI-015W-230-SC S = Single phase C = Cable

ACCESSORIES¹



● C = customizations are offered on demand even for smaller quantities. Typical customizations are indicated with a green dot at column end. Please contact us for any customization request.

GEAR MOTOR DATA

		3	3.6	5	6	7.5	9	10	12.5	15	18	20	25	30	36	40	50	60	75	90	100	120	150	180	200	250	300	500	600	750	C
Gear ratio		3	3.6	5	6	7.5	9	10	12.5	15	18	20	25	30	36	40	50	60	75	90	100	120	150	180	200	250	300	500	600	750	●
Nominal torque	Nm	0.30	0.36	0.51	0.61	0.76	0.91	1.0	1.3	1.5	1.8	1.8	2.3	2.7	3.3	3.7	4.6	5.0²	5.0²	5.0²	5.0²	5.0²	5.0²	5.0²	5.0²	5.0²	5.0²	5.0²	5.0²	5.0²	5.0²
Nominal speed	rpm	400	330	240	200	160	130	120	96	80	67	60	48	40	33	30	24	20	16	13	12	10	8	6.7	6	4.8	4	2.4	2	1.6	
Nominal power	W	13	13	13	13	13	13	13	13	13	13	11	11	11	11	11	11	10	8	7	6	5	4	3	3	2.5	2.1	1.3	1.0	0.84	
Gearb. nom. torq.³	Nm	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	5	
Gearbox efficiency	%	81	81	81	81	81	81	81	81	81	81	73	73	73	73	73	73	66	66	66	66	66	66	66	66	59	59	59	59	59	
Radial load⁴	N	120	120	120	120	120	120	120	120	120	120	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	250	
Direction of rot.		CW	CW	CW	CW	CW	CW	CW	CW	CW	CW	CCW	CCW	CCW	CCW	CCW	CCW	CW	CW	CW	CW	CW	CW	CW	CW	CCW	CCW	CCW	CCW	CCW	
Weight	kg	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	1.6	


OTHER GEAR MOTOR DATA

Service life	h	10000	C
Performance tolerances		± 15	
Operating temperature	°C	-10 to 40	
IP rating		IP20	
Manufacturing standard		ISO 9001	
CE label UL label		Yes No	

GEARBOX DATA

Shaft axial load	N	40	C
Bearing type		Ball bearing	
Shaft material		40 Cr steel	
Housing material		Aluminum	
Material gear stage		40 Cr steel	

WIRING DIAGRAM AC INDUCTION MOTOR



AC INDUCTION MOTOR DATA

Nominal voltage	V	230	C
No. of phases		1	
Frequency	Hz	50	
No. of poles		4	
Nominal speed	rpm	1200	
Nominal torque	mNm	125	
Nominal current	A	0.2	
Nominal power	W	15	
Stall torque	mNm	90	
Insulation class		B	
Motor cable		AWG20	
Motor cable length	mm	300	
Capacitor included in delivery	μF	1.2	
Insulation resistance	MΩ	100	
Dielectric strength	kV	1.5	
Max. winding temperature	°C	80	
Weight	kg	1	


GEAR MOTOR RANGE AI-SERIES⁵

Nominal voltage	V	See separate datasheet
Nominal power	W	See separate datasheet
Dimension	mm	See separate datasheet


NOTES

- See page 2 of this catalog.
- Gear motor torque limited by gearbox.
- Gearbox nominal torque.
- 20 mm from shaft.
- Visit www.transmotec.com to view datasheets.

DECIMAL GEARBOX¹




OUTPUT SHAFT D-CUT



DECIMAL GEARBOX DATA		
Model designation		S70A-Y010
Gear ratio		10:1
Nominal torque	Nm	5
Description		
Connected between AC motor and existing gearbox to decrease the speed further than the gear ratio listed in the table.		

DECIMAL GEARBOX DATA	
Model designation	Contact us for more information.

POWER CABLE



POWER CABLE DATA	
Model designation	
ACEU-020-0 ACUS-020-0	
Standard	EU CEE 7/7 US NEMA 5/15
Cable length	m ft
2 8	

NOTES	
1. Visit www.transmotec.com to view datasheets.	